

Extruded Aluminum Penthouse Elevator Vent - Model PEV-04

STANDARD CONSTRUCTION

ALL MATERIAL - EXTRUDED ALUMINUM 6063-T5 (KB-45)

FRAME

.081" thk. extruded aluminum

BLADES

.081" thk. extruded aluminum

ROOF

.063" formed aluminum (5005-H34), undercoated with black tar for anti-condensation

Size

38 x 38 x 18 (OD)

Glass

1/8" Annealed Glass one side

FASTENERS

Plated steel screws

CURB

36" Tall 16 Gauge Galvanized Steel Welded

UNDERSIZED

1/4" under ordered size unless specified Exact or Actual SCREEN

3/4" x .051" expanded aluminum bird screen

FINISH


Mill

Damper


29" x 29" UL listed model 621 smoke damper Class 1 with 120V electric actuator mounted internally

OPTIONAL CONSTRUCTION

BLADES, FRAME & ROOF - Available in heavier gauge material SCREEN - Many styles available please consult screen listing FINISH - Powder coat, epoxy primer, Kynar, or Powder coat. CONSTRUCTION - Fully welded construction



Post Corners



STANDARD CONSTRUCTION

MODEL: P-LEC-04-X00T-D
FRAME: .081" THK. EXTRUDED ALUM. ALLOY
6063-T52.
BLADES: .081" THK. EXTRUDED ALUM. ALLOY
6063-T53, © 45 DEGREES
CORNERS: .083" THK. FORMED ALUM. ALLOY
5005-H34
ROOF: .063" THK, FORMED ALUM. 5005-H34
UNDERCOATED WITH BLACK TAR
SCREEN: EXP. ALUM. SCREEN NO FRAME
FINISH: MILL

MODEL-622 CONSTRUCTION

Model: 622 — Smoke Damper Frame: 4–5/16" deep 16 ga. galvanized Steel Blades: 6" wde 16 ga. galvanized Steel Axle: 7/16" Plated Hex Bearings: Bronze Oil Impregnated LINKAGE: PLATED STEEL CONCEALED INSIDE JAMB DRIVE
SEALS: SILICONE, BLADE SEALS AND S.S. SIDE SEALS
ACTUATOR: SIENENS GGD-221, 120VAC

CURB CONSTRUCTION

MODEL: FRC-CS - ROOF CURB
SHELL: 16 GA. GALVANIZED STEEL
BASE: 16 GA. GALVANIZED STEEL
WOOD NAILER: AS REQUIRED, FACTORY INSTALLED
FASTENERS: WELDED CONSTRUCTION
INSULATION: 3-LBS. PCF DENSITY FIBERGLASS
THICKNESS: 1-5/8* THICKNESS: FINISH: MILL

NOTES:

1. ALL LOUVERS TO BE FABRICATED 1/4" UNDER USTED OPMS SIZES UNLESS SPECIFIED "ACTUAL". 2. ALL OPMS SIZES TO BE FIELD VERIFED AND GUARANTEED BY OTHERS PRIOR TO FABRICATION. 3. OTHER SURROUNDING FINISHES ARE FOR REFERENCES ONLY AND TO BE SUPPLIED BY OTHERS.

TAG	QTY OPENING SIZE (WXH) NOTES					
	2	38" X 38" X 18"	3-SDED LOUNCE WALL 1-SDE GLASS PANEL BY DTHERS			

DATE	ARCHITECT / ENGINEER			C	CUSTOMER			
PROJECT								
ITEM	QTY	w	Н	DESCRIPTION				



DEPENDABLE PRODUCTS SINCE 1955

SAFE-AIR / DOWCO

Engineering and General Offices 1855 South 54th Avenue / Cicero, Illinois 60804 Phone: 708-652-9100 FAX: 708-652-9158